ELSEVIER

Information Processing Letters 56 (1995) 15–17

Information
Processing
Letters

Efficient learning with equivalence queries of conjunctions of modulo functions [1]

Alberto Bertoni [2], Nicolò Cesa-Bianchi *, Guido Fiorino
DSI, Università di Milano, Via Comelico 39, 20135 Milano, Italy

Received 13 February 1995; revised 3 June 1995
Communicated by P.M.B. Vitányi

Abstract

A modulo m function takes value 0 when the weighted sum of the input variables is congruent to 0 mod m and takes value 1 otherwise. In this work we show a polynomial time algorithm for learning with equivalence queries the class of conjunctions of modulo p functions on n variables, for any fixed prime p. The result is also extended to learning with bounded adversarial noise.

Keywords: Learning with queries; Modulo functions; Analysis of algorithms

1. Introduction

For all positive integers m let Z_m be the class of residues modulo m. If n is a positive integer and w a vector in Z_m^n, we define the function $M_w : Z_m^n \to \{0,1\}$ by [3]

$$M_w(x) \overset{\text{def}}{=} \begin{cases} 0 & \text{if } w \cdot x \equiv 0 \bmod m, \\ 1 & \text{otherwise.} \end{cases}$$

Let $\{M_w : w \in Z_m^n\}$ be the class of *modulo m functions* over Z_m^n.

The class of modulo 2 (parity) functions was shown to be polytime learnable with at most n equivalence queries in [6,7]. In [4] the same number of equivalence queries was proven sufficient for learning the class of modulo p functions for any prime p. In [5] this was further extended to arbitrary disjunctions of modulo p functions, leaving open the corresponding problem for conjunctions. In this paper we solve the open problem by showing a polynomial time algorithm for learning the class of conjunctions of modulo p functions for any fixed prime p.

We will work in the "learning with equivalence queries" framework (see [1,8]). A problem in this framework is parametrized by a pair $(\mathcal{T}, \mathcal{H})$, where $\mathcal{T}$ is the *target class* and $\mathcal{H}$ is the *hypothesis class*, both containing $\{0,1\}$-valued functions defined on a common domain X and such $\mathcal{T} \subseteq \mathcal{H}$. Learning proceeds in trials. On each trial $t = 1, 2, \ldots$ the learning algorithm generates a hypothesis $H_t \in \mathcal{H}$. Afterwards, an element $x_t \in X$ (called *counterexample*) such that $T(x_t) \neq H_t(x_t)$ for a target $T \in \mathcal{T}$ satisfying $T(x_\tau) \neq H_\tau(x_\tau)$ for all $\tau = 1, \ldots, t-1$ is

---

* Corresponding author. Email: cesabian@dsi.unimi.it.

[1] A preliminary version of this paper appeared in the dissertation "Apprendimento di unione di piani nel modello PAC" presented by the third author to obtain the Italian Laurea degree.

[2] Email: bertoni@hermes.dsi.unimi.it.

[3] For all tuples u, v we write $u \cdot v$ to denote the componentwise sum $\sum_i u_i v_i$.

0020-0190/95/$09.50
SSDI 0020-0190(95)00126-3